# MATERIAL SAFETY DATA SHEET 01307

National Gypsum Company 2001 Rexford Road Charlotte, NC 28211

For emergency product safety information call, Director of Quality Services at 704-365-7543.

# I PRODUCT IDENTIFICATION

This material safety data sheet is applicable to the following Gold Bond® brand products:

Gauging Plaster
Gypsolite® Plaster
Kal-Kote® Base
Moulding Plaster
1-C Stucco
Plant Stucco
Two-Way Hardwall
Tectum Grout

Chemical Family: Mixture

#### II HAZARDOUS INGREDIENTS

Contains:	CACNO	OSHA	ACGIH
Chemical Identity	<u>CAS-NO</u>	<u>PEL</u> (mg/m³)	$\frac{\text{TLV}}{(\text{mg/m}^3)}$
Plaster of Paris	10034-76-1	5	$10^{A}$
Quartz <sup>B</sup>	14808-60-7	С	0.1
and may contain:			
Perlite	93763-70-3	5	$10^{ m A}$

Contains no asbestos. HMIS Hazard Class No. 1, 0, 0

Appearance and Odor

A white to gray powder with no odor.

Fire Hazard Data - Not combustible. NFPA Hazard Class No. 1, 0, 0

Extinguishing Media

Dry chemical, foam, water, fog or spray.

<sup>&</sup>lt;sup>A</sup> Total dust, all others are respirable dust.

<sup>&</sup>lt;sup>B</sup> Present as a naturally occurring component of minerals. See Sec. III HEALTH HAZARD DATA

<sup>&</sup>lt;sup>C</sup> Respirable dust, use the formula  $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ 

#### MATERIAL SAFETY DATA SHEET 01307

### Special Firefighting Procedures

Wear full protective equipment and an approved pressure demand self-contained breathing apparatus Reactivity Data

Gold Bond<sup>®</sup>Plaster Products are stable and hazardous polymerization will not occur. When heated to decomposition oxides of sulfur will be released.

#### III HEALTH HAZARD DATA

Quartz (crystalline silica)- The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.

It is recommended that a NIOSH approved respirator, for toxic dusts, be worn whenever working with this product results in airborne dust exposure exceeding the prescribed limits.

#### Skin Contact

Continued and prolonged contact may result in dry skin.

### **Eye Contact**

Direct contact may cause mechanical irritation.

#### Inhalation

Target Organ: respiratory system

# Signs and Symptoms of Exposure to Airborne Dust

Continued and prolonged exposure to airborne dust concentrations in excess of the PEL/TLV may result in cough, dyspnea, wheezing, and impaired pulmonary function.

# Medical Conditions Generally Aggravated by Exposure

Overexposure would generally aggravate respiratory system dysfunctions.

### First Aid Procedures

Eye: Immediately flush eyes with water for 15 minutes and get medical attention.

Skin: Flush and wash skin with soap and water. Get medical attention if irritation persists.

Breathing: Move the exposed person to fresh air at once. If not breathing initiate pulmonary resuscitation. Get medical attention.

#### MATERIAL SAFETY DATA SHEET 01307

#### IV PRECAUTIONS for SAFE HANDLING

Steps to be Taken in Case Material is Released or Spilled

Shovel or scoop up back into container for use if possible or disposal.

# Waste Disposal Method

Not a hazardous waste. Dispose of in accordance with applicable federal, state, and local regulations.

Precautions to be Taken in Handling and Storing

Keep from getting wet to preserve usefulness.

### V CONTROL MEASURES

Work/Hygiene Practices

Avoid creating dust.

#### Ventilation

Provide ventilation to maintain a dust level below the PEL/TLV.

# **Respiratory Protection**

A NIOSH approved respirator for toxic dusts is recommended if the PEL/TLV is exceeded.

## Eye Protection

Safety glasses or goggles..

#### VI REGULATORY INFORMATION

SARA Title III Section 313 Ingredients

None at or above the de minimus level.

Effective Date: January 26, 2001 Prepared by: Norbert W. Kaleta

# Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results

